

Mechanical characteristics

cables

interface dimensions acc. to assembly code
 center conductor
 outer conductor
 mating life

Components

center contact
 outer contact
 bayonet
 springwasher
 other metal parts
 insulator
 gasket

Electrical characteristics

impedance
 frequency
 working voltage
 voltage proof
 insulation resistance
 contact resistance
 center contact
 outer contact

Environmental

operating temp.
 RoHS compliant

Mechanische Eigenschaften

Kabel

Steckgesicht nach Montageanleitung
 Innenleiter
 Außenleiter
 Steckzyklen

Bauteile

Innenkontakt
 Außenkontakt
 Bayonett
 Federscheibe
 sonstige Metallteile
 Isolierung
 Dichtung

Elektrische Eigenschaften

Wellenwiderstand
 Frequenz
 Betriebsspannung
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

Betriebstemperatur
 RoHS konform

ⓑ **only for cable with solid inner conductor / nur für Kabel mit massivem Innenleiter**
 1.4/3.8 AF Draka, 7808A Belden, CNT-240 Andrew, HPF 240 Harbour Industries, S 04172 D Suhner, LMR-240 TMS, MRC 240 AFB Draka, SPEEDFOAM 240 HFJ Habia, SX 04172 B-60 Suhner TZC 500 25 Ericsson, WCX240 NEK/CDT

IEC 61169-8
 B98
 clamp / klemm
 clamp / klemm
 >500

Materials / Material

copper alloy/Kupferleg.
 brass/Messing
 zinc diecast/Zinkdruckguss
 copper alloy/Kupferleg.
 brass/Messing
 PTFE
 silicone/Silikon, NBR

Finish / Oberfläche


NiP Au
 Cu2Ni5
 Zn/Cu6Ni6
 Cu2Ni5
 Cu2Ni5/CuSnZn

50 Ω
 0-4 GHz
 ≤ 500V_{eff} / 50 Hz
 1,5 kV_{eff} / 50Hz
 ≥ 5 GΩ

≤ 20 mΩ
 ≤ 5 mΩ

ⓐ -30°C / +85°C
 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
				06.12.2016	BJ	
				15.12.2016	KL	ca./approx. 34
				Maßstab/ scale 2:1		
				Benennung/ title BNC Straight Plug, field mount type BNC-Kabelstecker, Feldmontage-Type		
				Zeichnungsnr./ drawing no. J01000A0071		
				Untert./ doc. type K		
				Ersatz für/ replaces		
				Maß/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1		
b	29732	04.07.2018	MA			
a	28410	16.01.2017	MA			



Maße/ dimensions: mm

Original : DIN A4

Blatt/ sheet 1 von/ of 1