



**Mechanical characteristics**  
cable group

**Mechanische Eigenschaften**  
Kabelgruppe

G43 (0,24/0,68); FWS 5022 Kurabe Industrial Co., Ltd,  
K 01152-7 Suhner, RF-MF5016 Nissei,  
Mini RF 1.13mm UL 1979 Weiyang Technology Co., Ltd

interface dimensions acc. to  
assembly code  
center conductor  
outer conductor

Steckgesicht nach  
Montageanleitung  
Innenleiter  
Außenleiter

IEC 60169-15  
J01150C0671  
solder / löt  
crimp

**Components**  
center contact  
outer contact  
other metal parts  
insulator  
gasket

**Bauteile**  
Innenkontakt  
Außenkontakt  
sonstige Metallteile  
Isolierung  
Dichtung

**Materials / Material**  
brass / Messing  
brass / Messing  
brass / Messing  
PTFE  
silicone / Silikon

**Finish / Oberfläche**  
gold plated / vergoldet  
gold plated / vergoldet  
gold plated / vergoldet

**Electrical characteristics**  
impedance  
return loss

**Elektrische Eigenschaften**  
Wellenwiderstand  
Rückflussdämpfung

50 Ω  
typ.: 1 GHz-33 dB; 2 GHz-28 dB;  
4 GHz-25 dB; 6 GHz-20 dB

**Environmental**  
RoHS compliant

**Umgebung**  
RoHS konform

2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
					02.06.2020	KL	
				gepr./ appr.	03.06.2020	PU	ca./approx. 3,6
Maßstab/ scale 5:1 (1:1)				Benennung/ title SMA Straight Plug SMA-Kabelstecker			
untol. Maße/ dim. without tolerances according to				Untert./ doc. type	Zeichnungsnr./ drawing no.		
				K	J01150C0671		
				Ersatz für/ replaces	J01150B0671		
							