



**Mechanical characteristics**

cables  
 interface dimensions acc. to assembly code  
     centre conductor  
     outer conductor  
 mating life

**Components**

centre contact  
 outer contact  
 crimp ferrule  
 other metal parts  
 insulator

**Electrical characteristics**

impedance  
 frequency  
 return loss  
 insertion loss  
 voltage proof  
 insulation resistance  
 contact resistance  
     centre contact  
     outer contact

**Environmental**

RoHS compliant

**Mechanische Eigenschaften**

Kabel  
 Steckgesicht nach Montageanleitung  
     Innenleiter  
     Außenleiter  
 Steckzyklen

**Bauteile**

Innenkontakt  
 Außenkontakt  
 Crimprohr  
 sonstige Metallteile  
 Isolierung

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Rückflussdämpfung  
 Einfügedämpfung  
 Prüfspannung  
 Isolationswiderstand  
 Durchgangswiderstand  
     Innenkontakt  
     Außenkontakt

**Umgebung**

RoHS konform

K 01252 D Suhner  
 CECC 22220  
 C2213  
 solder / löt  
 crimp  
 >100



**Materials / Material**

CuZn39Pb3  
 CuBe2Pb  
 SF Cu w  
 CuZn39Pb3  
 PTFE

**Finish / Oberfläche**

Cu1Ni2Au1,27  
 NiP Au  
 Ni5Au0,2  
 Cu2Ni5Au0,2



50 Ω  
 0-6 GHz  
 typ.: 1 GHz-39,5 dB; 2 GHz-36,5 dB; 3 GHz-34 dB  
 0,1 dB up to/ bis 3 GHz  
 750 V<sub>eff</sub> / 50 Hz  
 1 GΩ



2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight (g)
				06.03.2013	MA	
				08.03.2013	KL	ca./approx. 1,0
				Maßstab/ scale <b>5:1 (1:1)</b>		
				Benennung/ title <b>MCX Angle Plug                      MCX-Kabelwinkelstecker</b>		
				Untert./ doc. type	Zeichnungsnr./ drawing no.	
c	24678	06.03.2013	MA	K	J01270A0231	Maße/ dimensions: mm
b	10739	18.08.1999	HM			Original : DIN A4
a	10445	28.05.1999	HM	Ersatz für/ replaces	Zeichnung vom 23.07.1997	Blatt/ sheet 1 von/ of 1